



### USB Wall Sockets - Charge in Every Room

**TAIWAY USB Wall Sockets** with integrated charging ports provide a smarter and more efficient way to power your devices. Designed for **convenience**, **speed**, **and safety**, they free up traditional outlets while delivering reliable charging performance for both residential and commercial environments.

- Enhanced Safety Built-in overcurrent protection safeguards devices from overcharging and overheating, while tamper-resistant outlets prevent accidental insertion of foreign objects.
- Fast Charging Intelligent smart chip automatically detects and optimises power delivery, charging devices up to 50% in just 30 minutes.
- Commercial-Grade Quality Engineered to meet residential and commercial standards, ensuring durability and long-term reliability.
- Sustainable Design Forward-thinking, eco-friendly construction blends style, function, and sustainability, aligning with future energy-saving needs.







# USB Wall Outlet with Vertical Dual Type C High PD | Product Specification

Feature	Details
Charging Power	<ul> <li>Up to 60W on a single port (PD-enabled device)</li> <li>Up to 30W per port (60W total) when both ports are in use</li> </ul>
Maximum Outputs	5V/3A, 9V/3A, 15V/3A, 20V/3A (max 60W)
Charging Protocols	PD 3.0, BC 1.2, Apple Mode (2.4A)
Enhanced Circuit Protection (Built-in Circuit Protection)	OCP (Overcurrent Protection) OVP (Overvoltage Protection) OTP (Overtemperature Protection)OPP (Over Power Protection)SCP (Short Circuit Protection)
Operating Conditions	Ambient Temperature: -10°C ~ +40°C / Relative Humidity: 10% ~ 95%
Safety Regulations	CB, BSMI, PSE, IEC 62368
Customization	- Wall box dimensions customizable (MOQ: 100 pcs/order)- Wall plate colors: White & Black







## 60W USB Wall Socket with Vertical Dual Type A+C High PD | Product Highlight

Feature Description

Powerful Charging Up to 60W PD fast charging (USB-C up to 45W, USB-A up to 12W when both in use)

Multi-Protocol Support Compatible with PD 3.0, BC 1.2, Apple 2.4A

Universal Outputs 1 AC outlet + USB-C (5V–20V) + USB-A (5V/2.4A)

Comprehensive Safety OCP, OVP, OTP, OPP, SCP protections

Durable & Safe UL 94 V-0 fire rating; CB, BSMI, PSE, IEC 62368 certified

Flexible Design Customizable wall box dimensions (MOQ 100 pcs)

Modern Aesthetic Available in White & Silver-Gray finishes







#### 20W USB Wall Socket

### Marketing Highlights

- \( \nabla \) Fast PD Charging Supports PD 3.0 with up to 20W output for quick charging (0–50% in 30 minutes).
- 6 5-in-1 Protection Built-in OCP, OVP, OTP, OPP, SCP safeguards your devices from overcurrent, overheating, and short circuit.
- Stylish & Customisable Available in White or Silver Grey; wall box dimensions can be tailored (MOQ 100 pcs).
- © Certified Safety Meets CB, BSMI, PSE, and IEC 62368 standards with flame-retardant materials rated UL 94 V-0.








#### **65W USB-C Performance Test**

- •Test Setup: Sealed box, EU wall socket, no airflow
- •Scope: Efficiency, temperature rise, EMC, dimensions & pre-order
- •Key Highlights:
  - High efficiency, stable output
  - Controlled temperature, enhanced safety
  - EMC compliance ensures reliability
  - Compact design for versatile applications



#### **Competitor Comparison – Temperature Test**

**Focus**: Front panel surface temperature curves **Competitors Tested**: 65W / 45W / 25W models

**Results:** 

65W competitor: shut down due to overheating

45W competitor: stable but higher casing temperature

Our product: significantly lower panel temperature → safer & more durable

